



## Material Safety Data Sheet

Copyright, 2014, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**PRODUCT NAME:** SCOTCHKOTE 323 Purple Patch Compound  
**MANUFACTURER:** 3M  
**DIVISION:** Electrical Markets Division  
**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA  
**Telephone:** 1-888-3M HELPS (1-888-364-3577)

**EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)**

**Issue Date:** 10/13/14  
**Supersedes Date:** 04/21/14  
**Document Group:** 16-4389-9

### ID Number(s):

80-6300-0096-8, 80-6300-0179-2

**This product is a kit or a multipart product which consists of multiple, independently packaged components. An SDS for each of these components is included. Please do not separate the component SDSs from this cover page. The document numbers of the SDSs for components of this product are:**

16-4385-7, 16-4387-3

**Reason for Reissue:** The MSDS has been revised because 3M has adopted the 16-section ANSI/ISO format. The potential hazards of the product have not changed. We encourage you to reread the MSDS and review the information.

Revision Changes: Not Applicable

**DISCLAIMER:** The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at [www.3M.com](http://www.3M.com)



## Safety Data Sheet

Copyright, 2014, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	16-4385-7	<b>Version Number:</b>	5.00
<b>Issue Date:</b>	04/21/14	<b>Supersedes Date:</b>	02/20/12

### SECTION 1: Identification

#### 1.1. Product identifier

SCOTCHKOTE 323 Purple Patch Compound, Part A

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Part A of 2 Part Epoxy Coating

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Electrical Markets Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1.

Carcinogenicity: Category 2.

Specific Target Organ Toxicity (repeated exposure): Category 1.

#### 2.2. Label elements

##### Signal word

Danger

##### Symbols

Exclamation mark | Health Hazard |

##### Pictograms



**Hazard Statements**

Causes eye irritation.  
 May cause an allergic skin reaction.  
 Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure:  
 respiratory system |

**Precautionary Statements**

**Prevention:**

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Wear protective gloves.  
 Do not eat, drink or smoke when using this product.  
 Wash thoroughly after handling.  
 Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If eye irritation persists: Get medical advice/attention.  
 IF ON SKIN: Wash with plenty of soap and water.  
 If skin irritation or rash occurs: Get medical advice/attention.  
 Wash contaminated clothing before reuse.  
 IF exposed or concerned: Get medical advice/attention.

**Storage:**

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Hazards not otherwise classified**

None.

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER	25068-38-6	60 - 70 Trade Secret *
HYDROUS MAGNESIUM SILICATE	14807-96-6	20 - 30 Trade Secret *
TITANIUM DIOXIDE	13463-67-7	1 - 5 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### **Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### **Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### **If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Aldehydes	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion
Irritant Vapors or Gases	During Combustion
Ammonia	During Combustion
Oxides of Nitrogen	During Combustion

### 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Avoid eye contact. Avoid breathing of vapors created during cure cycle. Avoid skin contact with hot material. Avoid breathing of dust created by cutting, sanding, grinding or machining. For industrial or professional use only. Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

**7.2. Conditions for safe storage including any incompatibilities**

No special storage requirements.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
TITANIUM DIOXIDE	13463-67-7	Amer Conf of Gov. Indust. Hyg.	TWA:10 mg/m3	
TITANIUM DIOXIDE	13463-67-7	Chemical Manufacturer Rec Guid	TWA(as respirable dust):5 mg/m3	
TITANIUM DIOXIDE	13463-67-7	US Dept of Labor - OSHA	TWA(as total dust):15 mg/m3	
HYDROUS MAGNESIUM SILICATE	14807-96-6	Amer Conf of Gov. Indust. Hyg.	TWA(respirable fraction):2 mg/m3	
HYDROUS MAGNESIUM SILICATE	14807-96-6	Chemical Manufacturer Rec Guid	TWA(as respirable dust):0.5 mg/m3	
HYDROUS MAGNESIUM SILICATE	14807-96-6	US Dept of Labor - OSHA	TWA concentration(as total dust):0.3 mg/m3;TWA concentration(respirable):0.1 mg/m3(2.4 millions of particles/cu. ft.);TWA:20 millions of particles/cu. ft.	

Amer Conf of Gov. Indust. Hyg. : American Conference of Governmental Industrial Hygienists

American Indust. Hygiene Assoc : American Industrial Hygiene Association

Chemical Manufacturer Rec Guid : Chemical Manufacturer's Recommended Guidelines

US Dept of Labor - OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average  
STEL: Short Term Exposure Limit  
CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Provide ventilated enclosure for heat curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Wear protective gloves.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

#### Thermal hazards

Wear heat insulating gloves when handling hot material to prevent thermal burns.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>General Physical Form:</b>	Liquid
<b>Specific Physical Form:</b>	Viscous
<b>Odor, Color, Grade:</b>	Viscous, Light Brown
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>No Data Available</i>
<b>Melting point</b>	<i>No Data Available</i>
<b>Boiling Point</b>	<i>No Data Available</i>
<b>Flash Point</b>	> 200 °F [ <i>Test Method: Pensky-Martens Closed Cup</i> ]

Evaporation rate	< 1 [Ref Std: BUOAC=1]
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapor Pressure	No Data Available
Vapor Density	> 1 [Ref Std: AIR=1]
Density	No Data Available
Specific Gravity	1.43 [Ref Std: WATER=1]
Solubility In Water	Not Applicable
Solubility in Water	Nil
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity	120,000 centipoise [ @ 72 °C ] [Test Method: Brookfield]
Volatile Organic Compounds	12 g/l [Details: For coating mixture of Parts A and B]
Percent volatile	1.28 % volume
VOC Less H2O & Exempt Solvents	Not Applicable

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

None known.

### 10.6. Hazardous decomposition products

#### Substance

None known.

#### Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.



**11.1. Information on Toxicological effects**

**Signs and Symptoms of Exposure**

**Based on test data and/or information on the components, this material may produce the following health effects:**

**Inhalation:**

Vapors from heated material may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Vapors released during curing may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause target organ effects after inhalation.

**Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

**Target Organ Effects:**

**Prolonged or repeated exposure may cause:**

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

Ingredient	C.A.S. No.	Class Description	Regulation
TITANIUM DIOXIDE	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER	Dermal	Rat	LD50 > 1,600 mg/kg
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER	Ingestion	Rat	LD50 > 1,000 mg/kg
HYDROUS MAGNESIUM SILICATE	Ingestion		LD50 Not available
TITANIUM DIOXIDE	Dermal	Rabbit	LD50 > 10,000 mg/kg
TITANIUM DIOXIDE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
TITANIUM DIOXIDE	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER	Rabbit	Mild irritant
HYDROUS MAGNESIUM SILICATE	Rabbit	No significant irritation
TITANIUM DIOXIDE	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER	Rabbit	Moderate irritant
HYDROUS MAGNESIUM SILICATE	Rabbit	No significant irritation
TITANIUM DIOXIDE	Rabbit	No significant irritation

**Skin Sensitization**

Name	Species	Value
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER	Human and animal	Sensitizing
TITANIUM DIOXIDE	Human and animal	Not sensitizing

**Respiratory Sensitization**

Name	Species	Value
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER	Human	Some positive data exist, but the data are not sufficient for classification
HYDROUS MAGNESIUM SILICATE	Human	Not sensitizing

**Germ Cell Mutagenicity**

Name	Route	Value
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER	In vivo	Not mutagenic
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER	In Vitro	Some positive data exist, but the data are not sufficient for classification
HYDROUS MAGNESIUM SILICATE	In Vitro	Not mutagenic
HYDROUS MAGNESIUM SILICATE	In vivo	Not mutagenic
TITANIUM DIOXIDE	In Vitro	Not mutagenic
TITANIUM DIOXIDE	In vivo	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
HYDROUS MAGNESIUM SILICATE	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
TITANIUM DIOXIDE	Ingestion	Multiple animal species	Not carcinogenic
TITANIUM DIOXIDE	Inhalation	Rat	Carcinogenic

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER	Ingestion	Not toxic to female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER	Ingestion	Not toxic to male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER	Dermal	Not toxic to development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER	Ingestion	Not toxic to development	Rat	NOAEL 750 mg/kg/day	2 generation
HYDROUS MAGNESIUM SILICATE	Ingestion	Not toxic to development	Rat	NOAEL 1,600 mg/kg	during organogenesis

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
4,4'-ISOPROPYLIDENEDIPH ENOL-EPICHLOROHYDRIN POLYMER	Dermal	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	2 years
4,4'-ISOPROPYLIDENEDIPH ENOL-EPICHLOROHYDRIN POLYMER	Dermal	nervous system	All data are negative	Rat	NOAEL 1,000 mg/kg/day	13 weeks
4,4'-ISOPROPYLIDENEDIPH ENOL-EPICHLOROHYDRIN POLYMER	Ingestion	auditory system   heart   endocrine system   hematopoietic system   liver   eyes   kidney and/or bladder	All data are negative	Rat	NOAEL 1,000 mg/kg/day	28 days
HYDROUS MAGNESIUM SILICATE	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
HYDROUS MAGNESIUM SILICATE	Inhalation	pulmonary fibrosis   respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 18 mg/m <sup>3</sup>	113 weeks
TITANIUM DIOXIDE	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.010 mg/l	2 years
TITANIUM DIOXIDE	Inhalation	pulmonary fibrosis	All data are negative	Human	NOAEL Not available	occupational exposure

**Aspiration Hazard**

Name	Value

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information****Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA):** Not regulated

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - No    Pressure Hazard - No    Reactivity Hazard - No    Immediate Hazard - Yes    Delayed Hazard - Yes

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

## SECTION 16: Other information

### NFPA Hazard Classification

**Health: 2 Flammability: 1 Instability: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### HMIS Hazard Classification

**Health: \*2 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.**

Hazardous Material Identification System (HMIS® III) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® III ratings are to be used with a fully implemented HMIS® III program. HMIS® is a registered mark of the American Coatings Association (ACA).

<b>Document Group:</b>	16-4385-7	<b>Version Number:</b>	5.00
<b>Issue Date:</b>	04/21/14	<b>Supersedes Date:</b>	02/20/12

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**



## Safety Data Sheet

Copyright, 2015, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	16-4387-3	<b>Version Number:</b>	8.01
<b>Issue Date:</b>	05/12/15	<b>Supersedes Date:</b>	10/27/14

### SECTION 1: Identification

#### 1.1. Product identifier

SCOTCHKOTE 323 Purple Patch Compound, Part B

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Part B of 2 Part Epoxy Coating

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Electrical Markets Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 1.

Skin Corrosion/Irritation: Category 1B.

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 2.

Specific Target Organ Toxicity (respiratory irritation): Category 3.

Specific Target Organ Toxicity (repeated exposure): Category 1.

#### 2.2. Label elements

##### Signal word

Danger

##### Symbols

Corrosion | Exclamation mark | Health Hazard |

##### Pictograms



**Hazard Statements**

Causes severe skin burns and eye damage.  
 May cause an allergic skin reaction.  
 May cause respiratory irritation.  
 Suspected of damaging fertility or the unborn child.

Causes damage to organs through prolonged or repeated exposure:  
 respiratory system |

**Precautionary Statements**

**Prevention:**

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves, protective clothing, and eye/face protection.  
 Do not eat, drink or smoke when using this product.  
 Wash thoroughly after handling.  
 Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
 Continue rinsing.  
 Immediately call a POISON CENTER or doctor/physician.  
 If skin irritation or rash occurs: Get medical advice/attention.  
 Wash contaminated clothing before reuse.  
 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

**Storage:**

Store in a well-ventilated place. Keep container tightly closed.  
 Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Hazards not otherwise classified**

May cause chemical gastrointestinal burns.

8% of the mixture consists of ingredients of unknown acute oral toxicity.  
 8% of the mixture consists of ingredients of unknown acute dermal toxicity.  
 8% of the mixture consists of ingredients of unknown acute inhalation toxicity.

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
P-TERT-BUTYLPHENOL	98-54-4	20 - 30 Trade Secret *

HYDROUS MAGNESIUM SILICATE	14807-96-6	20 - 30 Trade Secret *
M-XYLENE-ALPHA,ALPHA'-DIAMINE	1477-55-0	5 - 15 Trade Secret *
PHENOL, 4-NONYL-, branched	84852-15-3	1 - 9 Trade Secret *
TRIMETHYLHEXAMETHYLENEDIAMINE	25620-58-0	5 - 15 Trade Secret *
PHENOL FORMALDEHYDE AMINE POLYMER	104242-08-2	5 - 15 Trade Secret *
VIOLET PIGMENT	6358-30-1	1 - 3 Trade Secret *
POLYAMIDE	Unknown	< 1.5 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

**Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

**Eye Contact:**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

**If Swallowed:**

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Ammonia	During Combustion
Oxides of Nitrogen	During Combustion

### 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.



**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

For industrial or professional use only. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep container tightly closed. Store away from acids. Store away from oxidizing agents.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
M-XYLENE-ALPHA,ALPHA'-DIAMINE	1477-55-0	ACGIH	CEIL:0.1 mg/m <sup>3</sup>	Skin Notation
HYDROUS MAGNESIUM SILICATE	14807-96-6	ACGIH	TWA(respirable fraction):2 mg/m <sup>3</sup>	A4: Not class. as human carcin
HYDROUS MAGNESIUM SILICATE	14807-96-6	OSHA	TWA concentration(as total dust):0.3 mg/m <sup>3</sup> ;TWA concentration(respirable):0.1 mg/m <sup>3</sup> (2.4 millions of particles/cu. ft.);TWA:20 millions of particles/cu. ft.	
HYDROUS MAGNESIUM SILICATE	14807-96-6	CMRG	TWA(as respirable dust):0.5 mg/m <sup>3</sup>	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration  
TWA: Time-Weighted-Average  
STEL: Short Term Exposure Limit  
CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Provide ventilated enclosure for heat curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield  
Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

#### Thermal hazards

Wear heat insulating gloves when handling hot material to prevent thermal burns.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>General Physical Form:</b>	Liquid
<b>Specific Physical Form:</b>	Viscous
<b>Odor, Color, Grade:</b>	Viscous, Purple
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>No Data Available</i>
<b>Melting point</b>	<i>No Data Available</i>
<b>Boiling Point</b>	> 200 °F

Flash Point	> 200 °F [ <i>Test Method:</i> Pensky-Martens Closed Cup]
Evaporation rate	< 1 [ <i>Ref Std:</i> BUOAC=1]
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	1 % volume
Flammable Limits(UEL)	7 % volume
Vapor Pressure	<i>No Data Available</i>
Vapor Density	> 1 [ <i>Ref Std:</i> AIR=1]
Density	<i>No Data Available</i>
Specific Gravity	1.18 [ <i>Ref Std:</i> WATER=1]
Solubility In Water	<i>Not Applicable</i>
Solubility in Water	Nil
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	20,000 [@ 72 °F] [ <i>Test Method:</i> Brookfield]
Volatile Organic Compounds	12 g/l [ <i>Details:</i> For coating mixture of Parts A and B]
Percent volatile	1.28 % volume
VOC Less H2O & Exempt Solvents	<i>Not Applicable</i>

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Not determined

### 10.5. Incompatible materials

Strong oxidizing agents

Reducing agents

### 10.6. Hazardous decomposition products

#### Substance

None known.

#### Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

**Signs and Symptoms of Exposure**

**Based on test data and/or information on the components, this material may produce the following health effects:**

**Inhalation:**

May be harmful if inhaled. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

**Skin Contact:**

May be harmful in contact with skin.

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

May cause additional health effects (see below).

**Eye Contact:**

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

**Ingestion:**

May be harmful if swallowed.

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

May cause additional health effects (see below).

**Additional Health Effects:**

**Single exposure may cause target organ effects:**

Dermal Effects: Signs/symptoms may include changes in skin pigmentation and/or coloration.

**Prolonged or repeated exposure may cause target organ effects:**

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE 2,000 - 5,000 mg/kg
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE 5 - 12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
P-TERT-BUTYLPHENOL	Dermal	Rabbit	LD50 2,318 mg/kg

P-TERT-BUTYLPHENOL	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.6 mg/l
P-TERT-BUTYLPHENOL	Ingestion	Rat	LD50 4,000 mg/kg
HYDROUS MAGNESIUM SILICATE	Dermal		LD50 Not available
HYDROUS MAGNESIUM SILICATE	Ingestion		LD50 Not available
M-XYLENE-ALPHA,ALPHA'-DIAMINE	Dermal	Rabbit	LD50 > 2,000 mg/kg
M-XYLENE-ALPHA,ALPHA'-DIAMINE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 1.2 mg/l
M-XYLENE-ALPHA,ALPHA'-DIAMINE	Ingestion	Rat	LD50 980 mg/kg
PHENOL, 4-NONYL-, branched	Dermal	Rabbit	LD50 > 2,000 mg/kg
PHENOL, 4-NONYL-, branched	Ingestion	Rat	LD50 1,531 mg/kg
TRIMETHYLHEXAMETHYLENEDIAMINE	Ingestion	Rat	LD50 910 mg/kg
VIOLET PIGMENT	Dermal	Rat	LD50 > 5,000 mg/kg
VIOLET PIGMENT	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
P-TERT-BUTYLPHENOL	Rabbit	Irritant
HYDROUS MAGNESIUM SILICATE	Rabbit	No significant irritation
M-XYLENE-ALPHA,ALPHA'-DIAMINE	Rat	Corrosive
PHENOL, 4-NONYL-, branched	Rabbit	Corrosive
TRIMETHYLHEXAMETHYLENEDIAMINE	Not available	Corrosive
VIOLET PIGMENT	Rabbit	Minimal irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
P-TERT-BUTYLPHENOL	Rabbit	Corrosive
HYDROUS MAGNESIUM SILICATE	Rabbit	No significant irritation
M-XYLENE-ALPHA,ALPHA'-DIAMINE	Rabbit	Corrosive
PHENOL, 4-NONYL-, branched	Rabbit	Corrosive
TRIMETHYLHEXAMETHYLENEDIAMINE	Rabbit	Corrosive
VIOLET PIGMENT	Rabbit	Mild irritant

**Skin Sensitization**

Name	Species	Value
P-TERT-BUTYLPHENOL	Human and animal	Some positive data exist, but the data are not sufficient for classification
M-XYLENE-ALPHA,ALPHA'-DIAMINE	Guinea pig	Sensitizing
PHENOL, 4-NONYL-, branched	Guinea pig	Not sensitizing
TRIMETHYLHEXAMETHYLENEDIAMINE	Guinea pig	Sensitizing

**Respiratory Sensitization**

Name	Species	Value
HYDROUS MAGNESIUM SILICATE	Human	Not sensitizing

**Germ Cell Mutagenicity**

Name	Route	Value
P-TERT-BUTYLPHENOL	In Vitro	Not mutagenic
HYDROUS MAGNESIUM SILICATE	In Vitro	Not mutagenic
HYDROUS MAGNESIUM SILICATE	In vivo	Not mutagenic
M-XYLENE-ALPHA,ALPHA'-DIAMINE	In Vitro	Not mutagenic
M-XYLENE-ALPHA,ALPHA'-DIAMINE	In vivo	Not mutagenic

PHENOL, 4-NONYL-, branched	In Vitro	Not mutagenic
PHENOL, 4-NONYL-, branched	In vivo	Not mutagenic
TRIMETHYLHEXAMETHYLENEDIAMINE	In vivo	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
P-TERT-BUTYLPHENOL	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
HYDROUS MAGNESIUM SILICATE	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
P-TERT-BUTYLPHENOL	Ingestion	Not toxic to male reproduction	Rat	NOAEL 600 mg/kg/day	2 generation
P-TERT-BUTYLPHENOL	Ingestion	Some positive female reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 600 mg/kg/day	2 generation
P-TERT-BUTYLPHENOL	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 70 mg/kg/day	2 generation
HYDROUS MAGNESIUM SILICATE	Ingestion	Not toxic to development	Rat	NOAEL 1,600 mg/kg	during organogenesis
M-XYLENE-ALPHA,ALPHA'-DIAMINE	Ingestion	Not toxic to female reproduction	Rat	NOAEL 450 mg/kg/day	1 generation
M-XYLENE-ALPHA,ALPHA'-DIAMINE	Ingestion	Not toxic to male reproduction	Rat	NOAEL 450 mg/kg	1 generation
M-XYLENE-ALPHA,ALPHA'-DIAMINE	Ingestion	Not toxic to development	Rat	NOAEL 450 mg/kg/day	1 generation
PHENOL, 4-NONYL-, branched	Ingestion	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 400 mg/kg/day	28 days
PHENOL, 4-NONYL-, branched	Ingestion	Toxic to female reproduction	official classification	NOAEL Not available	
PHENOL, 4-NONYL-, branched	Ingestion	Toxic to development	official classification	NOAEL Not available	
TRIMETHYLHEXAMETHYLENEDIAMINE	Ingestion	Not toxic to male reproduction	Rat	NOAEL 120 mg/kg/day	2 generation
TRIMETHYLHEXAMETHYLENEDIAMINE	Ingestion	Not toxic to development	Rat	NOAEL 120 mg/kg/day	2 generation
TRIMETHYLHEXAMETHYLENEDIAMINE	Ingestion	Some positive female reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 10 mg/kg/day	2 generation

**Lactation**

Name	Route	Species	Value
PHENOL, 4-NONYL-, branched	Ingestion	Rat	Does not cause effects on or via lactation

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
P-TERT-BUTYLPHENOL	Inhalation	respiratory irritation	May cause respiratory irritation	Rat	LOAEL 5.6 mg/l	4 hours
M-XYLENE-ALPHA,ALPHA'-	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for	Not available	NOAEL Not available	

DIAMINE			classification			
---------	--	--	----------------	--	--	--

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
P-TERT-BUTYLPHENOL	Ingestion	endocrine system   liver   kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 600 mg/kg/day	2 generation
P-TERT-BUTYLPHENOL	Ingestion	blood	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 200 mg/kg	6 weeks
HYDROUS MAGNESIUM SILICATE	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
HYDROUS MAGNESIUM SILICATE	Inhalation	pulmonary fibrosis   respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 18 mg/m3	113 weeks
M-XYLENE-ALPHA,ALPHA'-DIAMINE	Ingestion	endocrine system   blood   bone marrow	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 600 mg/kg/day	28 days
PHENOL, 4-NONYL-, branched	Ingestion	endocrine system   hematopoietic system   liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 400 mg/kg/day	28 days
PHENOL, 4-NONYL-, branched	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 150 mg/kg/day	90 days
PHENOL, 4-NONYL-, branched	Ingestion	heart   bone, teeth, nails, and/or hair   immune system   muscles   nervous system   respiratory system	All data are negative	Rat	NOAEL 150 mg/kg/day	90 days
TRIMETHYLHEXAMETHYLENEDIAMINE	Ingestion	hematopoietic system   liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 180 mg/kg/day	13 weeks
VIOLET PIGMENT	Ingestion	blood	All data are negative	Rat	NOAEL 500 mg/kg/day	6 weeks

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

**SECTION 12: Ecological information**

**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations**

**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. If no other disposal options are available, waste product

that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

This material contains a chemical which requires export notification under TSCA Section 12[b]:

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No</u>	<u>Regulation</u>	<u>Status</u>
PHENOL, 4-NONYL-, branched (Phenol, 4-nonyl-, branched)	84852-15-3	Toxic Substances Control Act (TSCA) 5 SNUR or Consent Order Chemicals	Proposed
PHENOL, 4-NONYL-, branched (Phenol, nonyl- )	84852-15-3	Toxic Substances Control Act (TSCA) 5 SNUR or Consent Order Chemicals	Proposed
PHENOL, 4-NONYL-, branched	84852-15-3	Toxic Substances Control Act (TSCA) 5 SNUR or Consent Order Chemicals	Proposed

This material contains a chemical subject to a proposed EPA Significant New Use Rule (TSCA Section 5)

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No</u>	<u>Reference</u>
PHENOL, 4-NONYL-, branched	84852-15-3	79 FR 59186

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: Other information



**NFPA Hazard Classification**

**Health:** 3 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None  
**Corrosive:** Yes

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**HMIS Hazard Classification**

**Health:** \*3 **Flammability:** 1 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® III) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® III ratings are to be used with a fully implemented HMIS® III program. HMIS® is a registered mark of the American Coatings Association (ACA).

<b>Document Group:</b>	16-4387-3	<b>Version Number:</b>	8.01
<b>Issue Date:</b>	05/12/15	<b>Supersedes Date:</b>	10/27/14

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**