



601 ZERO VOC LIQUID ADHESIVE

DESCRIPTION:

POLYGUARD 601 ZERO VOC LIQUID ADHESIVE is a fast drying, rubber based adhesive in solvent solution which is used in conjunction with **Polyguard** pipeline coatings and tapes. This product is formulated with VOC exempted solvents to meet all California VOC regulations.

PHYSICAL PROPERTIES	TYPICAL RESULTS
Color	Black
Solids Content (NVM)	Approximately 14 %
Flash Point	-5.9°C (21°F) Pensky Marten CC
Viscosity	800-1000 cps
Shelf Life	1 Year
Temperature Ranges	At Application 25°F. to 130°F (-4° to 54°C) In Service -25°F to 170°F (-32° to 66°C)
Weight Per Gallon	7.62 lb/gal
VOC g/l	0

APPLICATION:

601 ZERO VOC LIQUID ADHESIVE may be applied with roller or brush to clean and dry pipe surface. It should be applied at an average rate of 400 ft² per gallon (10m²/liter). **DO NOT THIN LIQUID ADHESIVE**. In the event of cold weather, store inside prior to use.

PRECAUTIONS:

The liquid adhesive is an industrial coating and would be harmful or fatal if swallowed. It is marked as red label from the standpoint of flash point. Prohibit flames, sparks, welding and smoking during application. Solvents could be irritating to the eyes. In case of contact with eyes, flush with water and contact physician.

Avoid prolonged contact with skin and breathing of vapor or spray mist from liquid adhesive. In confined areas, use adequate forced ventilation, fresh air masks, explosion proof equipment, and clean clothing.

This material is sold by **Polyguard Products, Inc.** only for the purposes described in this literature. Any other use of the products is the responsibility of the purchaser and **Polyguard Products** does not warrant nor will be responsible for any misuse of these products. **Polyguard Products** will replace material not meeting our published specifications within one year from date of sale.

This information is based on our best knowledge, but POLYGUARD cannot guarantee the results to be obtained.



Polyguard is ISO 9001 certified since 1996.

HEALTH AND SAFETY:

All **Polyguard Products** Safety Data Sheets (SDS) and precautionary labels should be read and understood by all user supervisory personnel and employees before using. Purchaser is responsible for complying with all applicable federal, state or local laws and regulations covering use, health, safety, and disposal of the product.

MAINTENANCE:

None required.

TECHNICAL SERVICE:

Protection Engineering

PO BOX 8996 - Pittsburg, CA 94565

PH: 925.427.6200

FAX: 925.427.6202

www.CorrosionCoatings.com