



Guard-Wrap™

Description:

Guard-Wrap™ consists of a spunbonded polyester mat saturated with microcrystalline wax that is laminated to a polyester film that is coated with microcrystalline wax. Its conformability makes it ideal for wrapping fittings. It also works well on straight pipe.

End Use:

Guard-Wrap can be used as a protective wrapper over various Trenton coatings such as Temcoat™, Innercoat®, and #1 Wax-Tape®. It offers mechanical protection from backfill and soil stress and provides an additional moisture barrier and increased dielectric strength.

Application Procedures:

Pre-apply the Trenton coating of choice and wrap Guard-Wrap over the coating, allowing for at least a 1" overlap. It is preferable to apply the dull side against the pipe and the smoother, film side against the soil. On straight pipe, Guard-Wrap can be spiral wrapped or cigarette wrapped and is applied with some tension. On irregular surfaces allow slack in the Guard-Wrap so it can be formed and molded to the contours of the surface.

Packaging:

Rolls are packaged in cardboard cartons, 50 square yards per carton.

6" x 150' rolls - 6 rolls/carton

9" x 150' rolls - 4 rolls/carton

12" x 150' rolls - 3 rolls/carton

18" x 150' rolls - 2 rolls/carton

Specifications:

Color	Brown
Polyester film thickness	.5 mil
Total thickness	10 - 14 mils
Dielectric strength	3500 volts (min)
Wax melt point	160 - 180° F

Advantages:

- Conformable to irregular shapes
- A two-part wrapper (plastic mat and film) for extra mechanical strength
- Withstands hot-application temperatures
- Resistant to chemicals and bacteria
- Composed of inert materials
- Excellent dielectric strength

Estimated Quantity Requirements:

Pipe Size	Guard-Wrap Sq. yds./100 ft. (1" overlap)
4	17
6	26
8	33
10	42
12	49

TRENTON

DISTRIBUTED BY:

PROTECTION
Pipeline Products, Protective Coatings & Cathodic Protection
ENGINEERING

2201 Harbor St, Unit C
Pittsburg, CA 94565
Tel: 800.878.8837

302 South 700 West
Pleasant Grove, UT 84062
Tel: 801.785.1546

www.corrosioncoatings.com info@corrosioncoatings.com