



# Poly-Ply™ Outerwrap



*Poly-Ply outerwrap is a multi-layer version of plastic wrap. It helps keep a separation between the tape and the soil.*

## Description:

Poly-Ply™ Outerwrap consists of three membranes of .5-mil clear, 50-gauge, poly-vinylidene chloride high-cling plastic, wound together as a single sheet. It provides a mechanical and electrical barrier and is flexible enough to conform to irregularly-shaped surfaces. It is inert, will not deteriorate, and is resistant to chemicals and bacteria commonly found in soil.

## End Use:

Poly-Ply Outerwrap can be used either as a wrapper directly over cold-applied Temcoat primer/coating or as an outerwrap over petrolatum-based or wax-based wraps, such as Trenton #1 Wax-Tape wrap. Because Poly-Ply is very conformable, it can be used on both straight pipe and irregular metal surfaces, such as T's and couplings.

## Specifications:

|                      |                |
|----------------------|----------------|
| Color:               | Clear          |
| Thickness:           | 1.5 mils       |
| Dielectric strength: | 2000 volts/mil |
| Water absorption:    | Negligible     |

## Application Procedures:

When applying Poly-Ply over Temcoat, simply wrap it over a thorough coating of Temcoat, being sure to overwrap by at least 1 inch. Because Poly-Ply adheres to itself, start and end each application with a tight, complete circling of the pipe or fitting, so that the outer layer of Poly-Ply always has a layer of Poly-Ply underneath to stick to securely. When using Poly-Ply as an outerwrap over a wrap, follow the same procedure.

## Packaging:

Coreless rolls are packaged in cartons containing 50 square yards per carton.  
4" x 50' rolls (27 rolls/carton)  
6" x 50' rolls (18 rolls/carton)  
9" x 50' rolls (12 rolls/carton)  
12" x 50' rolls (9 rolls/carton)  
18" and 36" widths available by special order.

## Advantages:


- 3-ply composition for extra mechanical strength
- High dielectric strength
- Conforms to irregular shapes
- Composed of inert plastic film that will not deteriorate
- Resistant to chemicals and bacteria
- Conveniently sized roll
- Relatively inexpensive

## Estimated Quantity Requirements:

| Pipe Size | Temcoat<br>Pounds/100 ft. | Poly-Ply<br>Square yards/100 ft. |
|-----------|---------------------------|----------------------------------|
| 4         | 74                        | 18                               |
| 6         | 110                       | 26                               |
| 8         | 152                       | 34                               |
| 10        | 190                       | 42                               |
| 12        | 226                       | 49                               |

# TRENTON

**DISTRIBUTED BY:**



2201 Harbor St, Unit C  
Pittsburg, CA 94565  
Tel: 800.878.8837

302 South 700 West  
Pleasant Grove, UT 84062  
Tel: 801.785.1546

[www.corrosioncoatings.com](http://www.corrosioncoatings.com)    [info@corrosioncoatings.com](mailto:info@corrosioncoatings.com)